IEA/LT Workshop (W59) combined with DOE/JAERI Technical Planning of Tokamak Experiments (FP1-2)

# Shape and Aspect Ratio Optimization for High Beta, Steady-State Tokamak

## Stability Calculations on NCT

(NCT: National Centralized Tokamak)

- G. Kurita and NCT design team: JAERI Naka
- J. Bialek and G.A. Navratil: Colombia University

#### **OUTLINE**

- 1) Analyses of Aspect Ratio and Plasma Shape ( $\delta$ : triangularity ) Effects on Critical  $\beta_N$
- 2) Resistive Wall Mode Analyses of NCT Plasma with Real Geometry of Stabilizing Plate and Vacuum Vessel
- ---- These calculations were performed using VALEN code in collaboration with Colombia University -----


## Effect of Shaping Factor on Critical β<sub>N</sub>

• Shaping factor has been considered to have increasing effect on critical  $\beta_N$ .

• Here, we investigate the effects of aspect ratio and triangularity deformation on critical  $\beta_N$ .


## Effect of Aspect Ratio on Critical β<sub>N</sub>

• Typical Up-Down Symmetric Equilibrium ( $\beta_N=5.5$ )




 $I_{p}$ =4[MA],  $B_{t}$ =3.7[T],  $\kappa$ =1.85 :  $\kappa_{95}$ =1.76,  $\delta$ =0.44 :  $\delta_{95}$ =0.35

- Negative Shear  $q_0/q_{95}/q_{min.} = 3.63/3.59/2.28,$   $q_0/q_{95} = 1.42/3.48,$ li(3)=0.48,  $p_0/=2.2$
- Positive Shear li(3)=0.56,  $p_0/=2.6$




 Profile's of safety factor, plasma current and plasma pressure

## Critical $\beta_N$ vs. Radius of Conducting Wall



- Smaller aspect ratio always give larger critical  $\beta_N$  for both cases.
- Negative shear plasm has larger stabilizing effect of conducting wall than positive shear plasma.


### Aspect Ratio Effect on Critical β<sub>N</sub> : n=2 mode



- Smaller aspect ratio always give larger critical β<sub>N</sub> values for n=2 mode also.
- Effect is reduced for large pressure peaking factor.


## Effect of Triangularity on Critical $\beta_N$ for Positive Shear Plasma

#### Typical Up-Down Symmetric Equilibrium (β<sub>N</sub>=2.5)




 $\kappa$ =1.97 :  $\kappa_{95}$ =1.84,  $\delta$ =0.14 :  $\delta_{95}$ =0.05

A=(R<sub>C</sub>/a=2.98/1.135=) 2.63, I<sub>p</sub>=2.5[MA], B<sub>t</sub>=2.15[T] 
$$q_0/q_{95}/q_{surf}$$
=1.59/5.21/7.17, Ii(3)=0.88, p<sub>0</sub>/=2.68



 Profiles of normalized plasma current and pressure and safety factor

## Shaping (δ:triangularity) Effect on Critical β<sub>N</sub>



- Change of equilibrium quantities with β<sub>N</sub>
- Equilibria are calculated with almost fixed  $q_{axis}$  (=1.6) and  $q_{95}$  (=5.2) values.

# Summary & Next Steps for "Shaping Effect" Analyses

• By choosing appropriate q values,  $q_{axis}$ ,  $(q_{min})$  and  $q_{95}$ , critical  $\beta_N$  values are shown to be increased by increasing S value (through aspect ratio or triangularity) for the pressure and current profiles considered here.


#### We must investigate

- Elongation effect
- Influence of plasma current and pressure profile for the shaping factor to increase critical  $\beta_N$

#### Resistive Wall Mode Analyses of NCT Plasma

- To get higher  $\beta_N$  values than no-wall  $\beta_N$  limit, to suppress or control Resistive Wall Mode is necessary.
- Critical  $\beta_N$  analyses of NCT plasma for n=1 mode using VALEN code are performed with real geometry of the stabilizing plate and vacuum vessel with finite conductivity.
- Critical  $\beta_N$  values for passive effect of stabilizing plate and vacuum vessel, and also with the effect of active feedback control are obtained.


## Cut Away View of Vacuum Vessel, Stabilizing Plate and Sector Coils of NCT




 There are many supports of stabilizing plate to vacuum vessel, which are not shown in the figure.

#### **Benchmark between DCON & ERATO-J**

#### Conformal ideal wall






**Equilibrium Comparison** 

**Stability Diagram** 

#### Double-Null Equilibrium for NCT Plasma



Parameters

$$\beta_{N}$$
= 5.0  
A=(R<sub>C</sub>/a=2.94/0.83=) 3.54  
I<sub>p</sub>=2.03[MA], B<sub>t</sub>=1.84[T]

 $\kappa = 1.97 : \kappa_{95} = 1.89$ 

 $\delta$ =0.41 :  $\delta$ <sub>95</sub>=0.32


 $q_0/q_{95}/q_{min.}=3.89/3.36/2.30$ 

 $Ii(3)=0.45, p_0/=2.18$ 

 Up-down symmetric double-null equilibria shown are used in the following critical beta analyses.

### Passive Stabilizing Effect of Stabilizing Plate

---- with and without holes and edge cut outs ----





δφ: phase shift between mode and holes and cut outs

- Growth Rates are increased by considering holes and edge cut outs in stabilizing plate and reduces ideal  $\beta_N$  limit about 8%.
- They are further increased by considering phase shift between mode and holes and edge cut outs in stabilizing plate.

#### **Eddy Current Pattern on Stabilizing Plate**








• Distortion of eddy current pattern increases the growth rates.

## Passive Growth Rate for Different Vacuum Vessel Models




 minor radii of vacuum vessel and stabilizing plate at equatorial plane

$$r_{V. V.}$$
 /a = 2.04  
---> Critical  $\beta_N \sim 3$   
 $r_{S. p.}$  /a = 1.31  
---> Critical  $\beta_N \sim 6$ 

from conformal wall analyses by DCON

 Passive structure provides most of the passive stabilization and the vacuum vessel wall is a secondary effect.

### Critical BN with Active Feedback Control



$$V_{coil} = G_p \Phi_{sensor}$$

- G<sub>p</sub> is proportional gain.
- Φ<sub>sensor</sub> is perturbed poloidal flux detected by poloidal field sensor placed at center of each coil.

$$C_{\beta} = \frac{\beta_{N}^{\text{critical}} - \beta_{N}^{\text{no-wall}}}{\beta_{N}^{\text{ideal-wall}} - \beta_{N}^{\text{no-wall}}}$$

- Maximum critical  $\beta_N$  with active feedback control for the present design of NCT plasma is 3.8, which corresponds to  $C_{\beta}$ =0.37.
- Without holes and edge cut outs, ideal  $\beta_N$  limit is expected to be increased to about 6, almost hits the  $\beta_N$  limit by DCON.

# Summary & Next Steps for "Real Geometry" Analyses

- Maximum critical  $\beta_N$  with active feedback control, obtained as a first step for present design of NCT plasma, is 3.8, which corresponds to  $C_{\beta}$ =0.37.
- To increase critical  $\beta_N$  values by changing the design of "Sector" coils to improve response time of feedback field to the plasma
- To obtain critical  $\beta_N$  for single-null equilibria