



Plasma Power Handling Parameters and Issues

May 1-3, 2000

M. Ulrickson

Presented at the FIRE Physics Workshop

Sandia is a multiprogram laboratory operated by Sandia Corporation, a Lockheed Martin Company,
for the United States Department of Energy under contract DE-AC04-94AL85000.





Outline

- **Power Distribution**
- **Divertor Heat Loads**
- **Divertor Conceptual Design**



Power Distribution

- **Heating Power - 30 MW**
- **Fusion Power - 200 MW (9 MW/m³)**
- **Alpha Power - 40 MW**
- **Thermal Power - 70 MW**
- **Assume:**
 - 30% power radiated in core
 - 30% power radiated in the scrape-off layer
- **Divertor Power - 34 MW**



Power Distribution

- **Assume:**
 - Inner divertor gets 20%
 - Equal up/down split for double null divertor
- **Divertor power distribution**
 - Inner - 7 MW (3.4 each)
 - Outer - 27 MW (14 each)



Divertor Heat Loads

- **The plasma edge has been modeled using the UEDGE code**
- **The inner divertor is easily detached assuming no impurity content**
- **The heat loads for an attached plasma in the outer divertor are 20-25 MW/m²**
- **Beryllium and/or neon must be added to the outer divertor to attain detachment**
- **The heat loads for a detached outer case are less than 5 MW/m²**



Divertor Heat Loads

- For a tungsten thickness of 7 mm the peak surface temperature is 1840C (for 5 mm it is 1400C)
- Steady-state temperatures are reached in about 1-2 sec for the cooling parameters assumed.



Peaking Factors On The Heat Flux

- **Misalignments are of three types**
 - Eccentricity of the TF and the divertor surface ($m=1$)
 - Misalignments between modules (TF coil period)
 - Accuracy of divertor module fabrication (high frequency)



Misalignment Peaking Factors

- For the $m=1$ eccentricity the peaking factor is typically 1.2 for a 5 mm displacement
- For module to module in the divertor ($n=16$) the key decision is whether four quadrant operation is desired
 - If yes, both leading edges will have to be recessed (like the TFTR bumper limiter)
 - If no, only one leading edge needs to be protected (a 5 mm step height yields a peaking factor of 1.09)



Disruption Heat Loads

- **Thermal Quench Phase**
 - 33 MJ stored thermal energy
 - Loss time 0.2 ms
 - Heated area in the divertor
 - Inner - $9.35 \text{ l}_E \text{ m}^2$
 - Outer - $10.9 \text{ l}_E \text{ m}^2$
 - Energy Scrape-off length 1.8-2.3 cm
 - Angle of incidence: outer - 30° and inner - 90°
 - Ratio of heated length: 1 to 3
 - In/out ratio: 1/2
 - Toroidal peaking: 2:1



Disruption Heat Loads

- Thermal Quench
- Energy deposition on the divertor plates
 - Inner: 8.5 to 21.8 MJ/m² or 42.5 to 109 GW/m²
 - Outer: 7.3 to 18.7 MJ/m² or 36.5 to 93.5 GW/m²
- These heat fluxes will cause the tungsten surface to melt in about 50 ns after the start of the disruption




Materials Capabilities

- Both the first wall and inner divertor can be passively cooled for a 10 sec pulse
- Recent results from the ITER R&D program have shown that both W and CFC can be used for actively cooled components up to 30 MW/m²
- These designs use either a monoblock or rod type configuration on a copper alloy heat sink that is water cooled.



Tungsten Rod PFC Mockup





Tritium Issues

- Both TFTR and JET have found that about 50% of the tritium injected into the machine is trapped in layers of redeposited carbon
- There is no acceptable method for removing such trapped tritium
- This has been identified as a major R&D issue for the continuation of ITER
- Recommendation: **DO NOT use carbon based materials in FIRE**




Materials Selection

- **For the divertor**
 - Inner divertor: W rods passively cooled
 - Outer divertor: W rods actively cooled
- **For the First Wall: Be plasma sprayed on cooled copper passive plates**



Allowed Pulse Duration for Passive Cooling





Divertor Conceptual Design

- **Modular construction for remote maintenance**
- **Actively cooled outer divertor**
- **Passively cooled baffle and inner divertor for baseline case (longer pulses or radiative outer solution will require active cooling of the baffle)**
- **Analysis of disruption forces is not complete**




Component Layout

- Relatively open configuration is forced by the proximity of the x-point
- Flux surface spreading is about X6
- The x-point to plate distances are 300 mm outside and 150 mm inside
- The outer divertor plate is at about 60 degrees to the field lines
- The inner divertor plate is nearly perpendicular to the field




FIRE Divertor Design






Outer Divertor Module






Divertor Module Construction





Outer Divertor Module





Conclusions

- The physics requirements for the FIRE divertor are challenging.
- Solutions have been found for the design of the plasma facing components
- It is recommended that the divertor be tungsten rods on a copper backing plate with active cooling on at least the outer divertor
- Further analysis of disruption effects is needed



Halo Currents

- Taking either a peaked or a uniform distribution gives the same halo current in the worst location.
- For 16 divertor modules the maximum halo current is 200 kA.
- Module size
 - Inner poloidal length: 0.58 m current path: 0.14 m
 - Outer poloidal length: 0.68 m current path: 0.41 m
- The force exerted on a module is
 - Inner: 0.3 MN
 - Outer: 0.77 MN



Eddy Currents

- The force on the edge of an outer plate is about 1.9 MN
- The force on the edge of an inner plate is about 2.8 MN
- This is a 2.5 times the halo load for the outer and 8.5 times the inner halo load
- Mitigating factors
 - The copper surface is not continuous
 - The stainless steel backing will need to be slotted
 - The convoluted path will add resistance



Particle Pumping Requirements

- **Loss of particles from the plasma:**
 - Number of particles in the plasma 1×10^{22}
 - Energy confinement time 0.5-0.8 s (use 0.65 s)
 - Particle confinement time $2-10 \tau_E$
 - Fueling rate required $3.1 \times 10^{21}/s$ ($1.25-10 \times 10^{21}/s$)
 - Assuming the fueling efficiency is 50% implies $6.2 \times 10^{21}/s$ (23 Pa m³/s; range 10-75 Pa m³/s)
- **Recommendation 75 Pa m³/s maximum fueling rate (net equal D and T)**



Particle Pumping Requirements

- **Particle pumping rate required for He removal**
 - Fusion burn rate $1 \times 10^{20}/s$ (200 MW)
 - He fraction in the divertor 0.02
 - Wall recycling coefficient 0.5
 - Required divertor pumping is $1.4\text{-}2.7 \times 10^{22}/s$ (50-100 Pa m³/s)
 - Very similar to the previous estimate
- **Recommendation provide pumping for up to 100 Pa m³/s**